Dear John:  Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the positive of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA/DoD		Approved For Release 2002/08/20 : CIA-RDP78B04747A002700030092-9	
Dear John:  Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the positive of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA/DoD			
Dear John:  Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the positive of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA/DoD			
Dear John:  Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the positive of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA/DoD			
Dear John:  Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the positive of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA/DoD			
Dear John:  Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the positive of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA/DoD			
Dear John:  Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the pigitizer is representative of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA / DoD			STA
Enclosed is a preliminary draft of the Stereo Chip Comparator along with some sketches of the outline.  There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the pligitizer is representative of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA/DoD			STA
There are two approaches to mounting the machine for use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the pigitizer is representative of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA / DoD		Dear John:	
use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of questions to which we need answers.  The enclosed photograph of the pigitizer is strepresentative of the unit we will soon commercialize.  For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on stereo Viewer. You may see the unit in operation ST  Declass Review by NIMA/DoD		Enclosed is a preliminary draft of the <u>Stereo Chip</u> Comparator along with some sketches of the outline.	
For your application, we will simply remove the cover from the small box and mount the traveling corner cube prism on the X and Y axis ways of the stereo chip comparator.  The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA / DoD		use. The first is to make small portable or movable table on casters with the machine isolated from the base through some sort of vibration isolators. The second is to modify the top of an office desk to support the machine so that the available drawer can be used to store accessories or use the adjacent top surface to place the work at hand. The desk would also have to be isolated from ambient surrounding vibrations. However, this last approach results in a somewhat more bulky unit if space is at a premium. The description output of the machine to the computer has been left out because of	l
The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.  Enclosed are two copies of descriptive literature on the Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA / DoD		The enclosed photograph of the Digitizer is representative of the unit we will soon commercialize.	STA
Enclosed are two copies of descriptive literature on the Stereo Viewer. You may see the unit in operation  Declass Review by NIMA / DoD  ST		from the small box and mount the traveling corner cube prism on the	
Stereo Viewer. You may see the unit in operation  ST  Declass Review by NIMA / DoD		The visual output counter unit would simply have two counters mounted one above the other in a slightly larger cabinet.	
		Enclosed are two copies of descriptive literature on Stereo Viewer. You may see the unit in operation	STA
ет		Declass Review by NIMA / DoD	
et.			
СТ			
	Γ		STA

Approved For Release 2002/08/20 : CIA-RDP78B04747A002700030092-9

	Approved For Release 2002/08/20 : CIA-RDP78B04747A002700030092-9	
STAT		
STAT	-2- 19 November 1962	
STAT	at U. S. Naval Photographic Interpretation Center by contacting  fo our knowledge, the unit performance is very successful.	
STAT	I have also included a copy of a Stereoscope Viewer with Fiber Optics Transmission. This unit is a take-off without the cabinet, loop forming devices, etc. However, all the fine high resolution optics have been retained.	STAT
	Very truly yours,	
<u> </u>	ARB:efs	STAT
STAT	Encl: Literature (2) Literature (1) Photographs (2) Sketches	
STAT		